

ABOUT HPOWER

hpower actuators combine fastest response times in μs , superior kHz dynamics, high force generation in the range of tens of kN and nanometer precision in a way that is unmatched by any other linear driving system. The actuation can be obtained without any mechanical wear, making the actuators extremely durable. hpower products include ring and stack type actuators, as well as shakers and shock generators. hpower is the result of the collaboration between piezosystem jena and Piezomechanik GmbH and therefore combines centuries of piezo expertise with new innovations.

STACK TYPE ACTUATORS SERIES PSt 1000/25

SERIES PST WITHOUT CASING AND WITHOUT PRELOAD, DIAMETER 25MM



Concept

Solid stack type actuators are made based on a special smart material known as PZT ceramics. This enables these actuators to achieving outstanding performance with a motion range from $0\mu\text{m}$ to $260\mu\text{m}$ or even higher on request, while generating maximum force of up to 25kN. The actuators are available in different lengths, a stack with a length of 50 mm usually possesses a maximum motion of 50 - 70 μm (0.1% - 0.15% of the length).


Product highlights

- max. load: 35000 N
- max. force generation: 25000 N
- high stiffness
- high resonant frequency


Options

- low temperature modification
- ultra high vacuum (UHV) modification
- strain gage (SG) measurement system
- piezo material HP (high power & capacitance)

Applications:




MODAL ANALYSIS



VIBRATION CONTROL



MATERIAL TESTING




MECHANICAL ENGINEERING

Technical data of PSt 1000/25 series

type	motion, μm	voltage range, V	Length, mm	resonant frequency, kHz	Blocking force, N	Maximum load, N	Capacity, nF	Stiffness, $\text{N}/\mu\text{m}$
PSt 1000/25/07	7	0...+1000	9	60	25000	35000	140	1800
PSt 1000/25/20	20	0...+1000	18	40	25000	35000	350	900
PSt 1000/25/40	40	0...+1000	36	25	25000	35000	800	450
PSt 1000/35/60	60	0...+1000	54	20	25000	35000	1250	300
PSt 1000/35/80	80	0...+1000	72	15	25000	35000	1700	200

Technical drawing of PSt 1000/25 series



Get in touch with **us**
and we will help configuring
the best solution.

phone: +1 508-381-0425 (USA) +49 3641 6688-38 (GERMANY)

fax: +1 508-634-6868 (USA) +49 3641 6688-66 (GERMANY)

e-mail: givememore@hpowermotion.com